

UTILITY PATENT APPLICATION TRANSMITTAL

(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
YO998-527

Total Pages in this Submission

TO THE ASSISTANT COMMISSIONER FOR PATENTS

Box Patent Application

Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

QUIESCENT RECONFIGURATION OF A ROUTING NETWORK

and invented by:

Kevan L. Miller, Robert E. Strom, Daniel C. Sturman, Michael James Ward

If a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☒ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Enclosed are:

Application Elements

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 39 pages and including the following:
 - a. ☒ Descriptive Title of the Invention
 - b. ☒ Cross References to Related Applications (if applicable)
 - c. ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
 - d. ☐ Reference to Microfiche Appendix (if applicable)
 - e. ☐ Background of the Invention
 - f. ☒ Brief Summary of the Invention
 - g. ☒ Brief Description of the Drawings (if drawings filed)
 - h. ☒ Detailed Description
 - i. ☒ Claim(s) as Classified Below
 - j. ☒ Abstract of the Disclosure

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
YO998-527

Total Pages in this Submission

Application Elements (Continued)

3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*

- a. ☒ Formal Number of Sheets Eleven (11)
- b. ☐ Informal Number of Sheets _____

4. ☒ Oath or Declaration

- a. ☐ Newly executed *(original or copy)* ☒ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☒ With Power of Attorney ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application,
see 37 C.F.R. 1.63(d)(2) and 1.33(b).

5. ☐ Incorporation By Reference *(usable if Box 4b is checked)*

The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.

6. ☐ Computer Program in Microfiche *(Appendix)*

7. ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*

- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

Accompanying Application Parts

8. ☐ Assignment Papers *(cover sheet & document(s))*
9. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*
10. ☐ English Translation Document *(if applicable)*
11. ☒ Information Disclosure Statement/PTO-1449 ☒ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☒ Certificate of Mailing

☐ First Class ☒ Express Mail *(Specify Label No.):* EL311723229US

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
YO998-527

Total Pages in this Submission

Accompanying Application Parts (Continued)

15. ☐ Certified Copy of Priority Document(s) *(if foreign priority is claimed)*
16. ☐ Additional Enclosures *(please identify below):*

--

Fee Calculation and Transmittal


CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	41	- 20 =	21	x \$18.00	\$378.00
Indep. Claims	4	- 3 =	1	x \$78.00	\$78.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$760.00
OTHER FEE (specify purpose) _____					\$0.00
TOTAL FILING FEE					\$1,216.00

- ☐ A check in the amount of _____ to cover the filing fee is enclosed.
- ☐ The Commissioner is hereby authorized to charge and credit Deposit Account No. _____ as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of _____ as filing fee.
 - ☐ Credit any overpayment.
 - ☐ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
 - ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Dated: March 30, 1999

cc:



Kevin P. Radigan, Esq.
Reg. No. 31,789
HESLIN & ROTHENBERG, P.C.
5 Columbia Circle
Albany, NY 12203
Tel.: (518) 452-5600
Fax: (518) 452-5579

**QUIESCENT RECONFIGURATION OF
A ROUTING NETWORK**

Cross-Reference to Related Applications

5 This application contains subject matter which is
related to the subject matter of the following United States
patent applications, which are assigned to the same assignee
of this application. Each of the below-listed applications
is hereby incorporated herein by reference:

10 "Routing Messages Within A Network Using The Data
Content Of The Message," by Chandra et al., filed
November 20, 1997, serial no. 08/975,303;

15 "Message Logging For Reliable Multicasting Across
A Routing Network," by Banavar et al., co-filed
herewith, serial no. , (attorney docket no.
YO998-525);

 "Message Sequencing For Ordered Multicasting Of A
Message Across A Routing Network," by Banavar et al.,
co-filed herewith, serial no. , (attorney
docket no. YO998-526); and

20 "Non-Disruptive Reconfiguration Of A
Publish/Subscribe System," by Miller et al., co-filed
herewith, serial no. , (attorney docket no.
YO999-124).

Technical Field

This invention relates in general to reconfiguration of a routing network and, in particular, to quiescently reconfiguring a routing network having one or more special
5 nodes for facilitating reliable delivery or ordered delivery of messages within the routing network using logging or sequencing techniques employing the special node(s).

Background of the Invention

Many network environments enable messages to be
10 forwarded from one site within the network to one or more other sites using a multicast protocol. Typical multicast protocols send messages from one site to one or more other sites based on information stored within a message header. That is, each message has two components: the message
15 header, which includes the routing information, including destination addresses or a predefined group name that is associated with a fixed list of destinations, and a data content, which is the data of the message. The routing information is read from the message header and is used to
20 send the data content of the message to the specified destinations.

One example of a system that conventionally includes such a network environment is a publish/subscribe system. In publish/subscribe systems, publishers post messages and
25 subscribers independently specify categories of messages in which they are interested. The system takes the posted messages and includes in each message header the destination information of those subscribers indicating interest in the

particular message. The system then uses the destination information in the message to forward the message through the network to the appropriate subscribers.

5 More particularly, a publish/subscribe system includes a network of message routers (or simply routers or nodes) connected via links in an arbitrary graph topology. A number of clients connect to the periphery of this router network and either publish or subscribe to messages. A message includes of a number of attributes, which are name-
10 value pairs. A subscription specifies a predicate on the attributes of messages.

The problem addressed by the present application is how to handle changes of topology in such a routing network. The need for changing topology arises from a number of
15 conditions, including: (1) the need for system maintainers to move routers on- and off-line; (2) the growth of the network; and (3) changes in link speed that alter the optimum spanning trees of the network; etc. An assumption is made that a configuration manager has made a decision to
20 effect a particular topology change (i.e., a reconfiguration). The present invention is directed to a technique by which nodes of the router network execute a reconfiguration decision, eventually resulting in a new state of the network in which messages are forwarded using a
25 new spanning tree.

Disclosure of the Invention

Briefly summarized, the present invention comprises in one aspect a method for reconfiguring a routing network.

The method includes: quiescing the routing network to preserve a first-in first-out ordering of data messages within the routing network; and reconfiguring the quiesced routing network. As an enhancement, the method further
5 includes the quiescing of control messages within the routing network prior to the reconfiguring, and the routing network comprises a special network having at least one logging node or a sequencing node wherein messages are either logged to persistent storage for reliable routing or
10 sequenced with other messages received by the network for ordered delivery.

In another aspect, the invention comprises a system for reconfiguring a routing network. The system includes means for quiescing the routing network to preserve a first-in
15 first-out ordering of data messages within the routing network, and means for thereafter reconfiguring the quiesced routing network.

In still another aspect, a system for reconfiguring a publish/subscribe system is provided. This reconfiguration
20 system includes a routing network adapted to receive published messages for forwarding to subscribers. The network is further adapted to quiesce data messages and control messages within the network in response to a reconfigure command to preserve a first-in first-out
25 ordering of data messages and control messages within the routing network, and to then reconfigure the routing network once data messages and control messages have been quiesced.

In a further aspect, the invention comprises an article of manufacture which includes at least one computer usable

medium having computer readable program code means embodied therein for effecting reconfiguring of a routing network.

The computer readable program code means in the article of manufacture includes: computer readable program code means

5 for causing a computer to effect quiescing the routing network to preserve a first-in first-out ordering of data messages within the routing network; and computer readable program code means for causing a computer to effect reconfiguring the quiesced routing network.

10 To restate, provided herein is a technique for quiescent reconfiguration of a routing network of a publish/subscribe system without loss of messages. Reconfiguration is dynamic in that it is accomplished without shutting down the network, i.e., the execution of a
15 reconfiguration is not directly visible to either publishers or subscribers. The publishers and subscribers continue to publish and receive messages as if no reconfiguration is taking place or has taken place. As used herein, quiescent means that it is only necessary to temporarily suspend
20 message traffic within the routing network before reconfiguring the network and resuming message traffic. The quiescent reconfiguration technique presented has particular application in large, continuously available broker networks in which change and evolution are inevitable and service
25 disruption is not tolerable. Although principally described below in connection with a content-based routing network, the reconfiguration approach can be applied to other routing systems, e.g., subject-based routing systems.

Brief Description of the Drawings

The above-described objects, advantages and features of the present invention, as well as others, will be more readily understood from the following detailed description of certain preferred embodiments of the invention, when considered in conjunction with the accompanying drawings in which:

Fig. 1 depicts one example of a distributed network incorporating and using the quiescent reconfiguration capability of the present invention;

Fig. 2 depicts one example of a spanning tree used in accordance with the principles of the present invention;

Fig. 3 depicts one embodiment of a distributed router network, configured with resilient or ordered routing capability, which is to undergo quiescent reconfiguration in accordance with the present invention;

Fig. 4 depicts one embodiment of a router for use in accordance with the principles of the present invention in a router network such as depicted in **Fig. 3**;

Fig. 5 depicts one example of an information table for routers of a network employing quiescent reconfiguration in accordance with the principles of the present invention;

Fig. 6 is a flowchart of one embodiment of CONFIGURE message processing in accordance with the principles of the present invention;

Fig. 7 is a flowchart of one embodiment of QUIESCE message processing in accordance with the principles of the present invention;

Fig. 8 is a flowchart of one embodiment of
5 QUIESCE_ACKNOWLEDGE message processing in accordance with the principles of the present invention;

Fig. 9 is a flowchart of one embodiment of QUIESCE_SPECIAL message processing in accordance with the principles of the present invention;

10 **Fig. 10** is a flowchart of one embodiment of QUIESCE_SPECIAL_ACKNOWLEDGE message processing in accordance with the principles of the present invention;

Fig. 11 is a flowchart of one embodiment of QUIESCE_COMPLETE message processing in accordance with the
15 principles of the present invention; and

Fig. 12 is a flowchart of one embodiment for processing published messages in a routing network undergoing quiescent reconfiguration in accordance with the principles of the present invention.

20 **Best Mode for Carrying Out the Invention**

In one aspect, the present invention can be employed in a system using the routing capability disclosed in the above-incorporated application wherein messages are routed in a network based on the content of the data within the
25 message. With data-content routing, a message does not need

to include destination information, such as destination addresses or a group destination name. Instead, data within the message is used to traverse a data structure to determine the link or links over which the message is to be forwarded in order to reach the consumers (subscribers or clients) interested in the message.

More particular to the present invention, a quiescent reconfiguration technique is provided for, for example, such a content-based multicasting network. Further, the quiescent reconfiguration technique presented herein may be used in combination with, or separately from, the "reliable routing capability" and the "total ordering capability" described in the above-incorporated, co-filed patent applications. Whether used in combination with reliable routing or ordered delivery, or separately therefrom, quiescent reconfiguration in accordance with the principles of this invention may also be used with the above-described content-based routing network. However, those skilled in the art will recognize that the reconfiguration technique presented below is equally applicable to other routing systems, such as a subject-based routing system. One assumption underlying the reconfiguration technique is that links within the routing network propagate messages in a reliable first-in first-out manner.

One example of a distributed network 100 incorporating and using the quiescent reconfiguration capability of the present invention is depicted in **Fig. 1** and described in detail below. Network 100 includes, for instance, a plurality of computing units 102 coupled to one another by links 104.

Each link couples two computing units in the network, and each computing unit may have any number of links connected to it. Each link is bidirectional, i.e., a computing unit may send and receive messages on the link.

5 Each link is also connection oriented, i.e., the computer units at the ends of the link are notified when the link fails. Furthermore, each link propagates messages in a first-in first-out manner. Each computing unit in the network is either a client computer (represented by the
10 smaller ovals, such as those having addresses 101a, 101b), meaning that it either originates messages or has requested to receive messages whose content satisfies certain properties; or it is a router computer (represented by the larger ovals, such as 102a, 102b), meaning that it forwards
15 messages received on one network link onto other links on the way to the client computer(s). The clients are collectively referred to herein as clients 101 and the routers are collectively referred to as routers 102. (For purposes of this discussion, if a single computing unit
20 serves both as a router and as a client, these two separate functions will be considered as two computing units connected by a link.)

Each computing unit can be any type of computing unit that can be included in a network. For example, it can be
25 an RS/6000 computing node or any other of various types of computing nodes, processors, computers or systems. The network can also include different types of computing units coupled to one another via the links. The links include, for instance, TCP connections over IP links, as only one
30 example.

Distributed network 100 can be included in various systems that require the passing of messages or data. These systems include, for instance, the Internet or publish/subscribe systems (such as the above-summarized content-based messaging system).

Content-based publish/subscribe systems improve the degree of decoupling between publishers and subscribers. In content-based publish/subscribe systems, subscriptions are specified in terms of predicates on the posted data, rather than in terms of subject identifiers supplied by the publisher. One example of a content-based publish/subscribe system is described in co-pending U.S. Patent Application Serial No. 08/975,280, entitled "Method And System For Matching Consumers To Events," Astley et al., which is hereby incorporated herein by reference in its entirety. The examples described herein are with reference to a content-based subscription system. However, these are only examples. The present invention can be employed with other types of systems without departing from the spirit of the present invention.

In one embodiment of the invention, each router 102 of network 100 (**Fig. 1**) has associated therewith a spanning tree, which lays out the best path (according to some criterion, such as latency) from the router to each client 101. In this embodiment, it is assumed that routers agree on a common criterion for measuring distance between nodes in the network. There may in fact be multiple spanning trees. For example, alternative spanning trees may specify either backup routes, or peak load routes. Herein, it is

assumed that one spanning tree is initially in effect for the routing of any particular message.

One example of a spanning tree, which is associated with a router is depicted in **Fig. 2**. As shown in **Fig. 2**,
5 there is a path from a router 102a to every other node in the spanning tree. A message to be routed from router 102a to one or more of the other nodes is routed via one or more of the links associated with router 102a, i.e., links 1-3. For example, if a message is to be routed from node 102a to
10 node 101c, then link 2 is used. As a further example, if a message is to be forwarded toward client 101a, then link 3 is used.

One embodiment for building a spanning tree from a network topology, that is an arbitrary graph, is described
15 in detail in Introduction to Algorithms, by Cormen, Leiserson, Rivert, Chapter 24, pp 498-513, Published by MIT Press (1990), which is hereby incorporated herein by reference in its entirety.

In addition to the spanning tree associated with each
20 router, each router has a routing table. The routing table includes an entry for each client computer in the network. Each entry of the routing table associates a client address with the identifier of the network link constituting the next segment on the path in the spanning tree from the
25 router to the client. For a router with d network links, each such link identifier is an integer between 1 and d. For instance, the client having address 101a has a corresponding link identifier of 3 (see **Fig. 2**).

Each routing table is constructed via information from the network topology (e.g., the client addresses) and hence from the corresponding spanning tree (e.g., the link identifiers), in a known manner.

5

By way of example, **Fig. 3** depicts one embodiment of a publish/subscribe system, generally denoted 300, to employ quiescent reconfiguration in accordance with the principles of the present invention. System 300 includes a network of routers 302 connected via links 303 in an arbitrary graph topology. A number of clients connected to the periphery of this router network either publish messages or subscribe to messages. Those clients publishing messages comprise publishers 304, while those clients subscribing to messages comprise subscribers 306. The router network is responsible for routing messages from a publisher 304 to interested subscribers 306 based on matching messages to subscription predicates.

10

15

20

25

Again, this protocol (i.e., content-based routing) is described in detail in the initially-incorporated co-pending patent application entitled "Routing Messages Within A Network Using The Data Content Of The Message." As noted, from each router node at which a publisher is present, the system computes and stores a spanning tree to reach every other node in the network. All published messages from the publisher follow the paths in that spanning tree, with each router node performing enough matching to determine which of its child routers should receive the message.

30

Within a publish/subscribe system, the present invention can be employed, in one example, with a network

achieving reliability of routed messages by saving messages to persistent storage within the network (and then retrieving and redelivering the message whenever there is a failure in the network). Such a reliable routing network is described in the above-incorporated, co-filed patent application entitled "Message Logging For Reliable Multicasting Across A Routing Network." In accordance with that invention, publishers and subscribers that need reliability of messages may specify a quality of service parameter, e.g., "uniform delivery". Uniform delivery is provided for ensuring delivery of a message to all active subscribers notwithstanding failure in the network, e.g., the routers, or the links. One or more special routers in the router network 300 are designated logging node(s) or logger(s) 310 and support the ability to log messages to stable storage. When there is at least one subscriber needing logging, the routing algorithm ensures that messages are routed to the logger.

Alternatively, or in further combination, the present invention can be employed in another example with a network achieving ordering of routed messages by sequencing messages within the router network itself through assignment of a sequence number at a designated sequencing node of the network. Publishers and subscribers that need ordering of messages may specify a quality of service parameter called "totally ordered". Total ordering is provided for ensuring ordered delivery of a message to all active subscribers. Such message sequencing within the router network is described in the above-incorporated, co-filed application entitled "Message Sequencing For Ordered Multicasting Of A Message Across A Routing Network." When employing

sequencing, a special router 310 in the router network 300 is designated a sequencing node or sequencer. Node 310 supports the ability to sequence messages received into the routing network. When there is at least one subscriber
5 needing total ordering, the routing algorithm guarantees that messages are routed to the sequencer.

To summarize, quiescent reconfiguration pursuant to the present invention can be employed in a router network of a publish/subscribe system which utilizes at least one special
10 node to facilitate either, or both, logging of messages or sequencing of messages with the network itself.

Fig. 4 depicts one embodiment of a router node for use in accordance with the principles of the present invention. When a message arrives at router 400 it is stored into a
15 message table 402 using a unique message identifier. Information stored includes a source node identification as well as the neighboring nodes to which the message is to be forwarded. These neighboring nodes are calculated by a content routing computation component 404 after the message
20 has been received. Computation component 404 takes the message and, based upon stored subscriptions and the spanning tree, returns a set of destinations or links upon which the message should be forwarded. Again, in one embodiment, this computation is content dependent and can be
25 accomplished as described in the above-incorporated co-pending application. However, this component can be implemented in other ways, e.g., subject-based routing. In one embodiment, to facilitate reliable routing of messages, router 400 would also include a reliable routing component
30 406 and logging acknowledgment (LACK) received table 408 and

LACK send table 409, which are described in the above-incorporated, co-filed application entitled "Message Logging For Reliable Multicasting Across A Routing Network."

5 If ordered routing of messages is employed, then router 400 would also include recovery data, including a latest sequence number received and linked node tables (not shown) such as described in the above-incorporated, co-filed application entitled "Message Sequencing For Ordered Multicasting Of A Message Across A Routing Network." Again, 10 the quiescent reconfiguration approach of this invention can be employed in a routing network of a publish/subscribe system employing data content messaging, reliable routing of messages, or sequencing of messages, either individually or in combination.

15 Quiescent reconfiguration requires the entire routing network to be quiesced before the network is reconfigured and network operations are resumed. Since the network is quiesced before it is reconfigured, first-in first-out (FIFO) ordering is preserved between all nodes. In 20 accordance with this invention, once quiesced, a node may not publish any new messages from one or more clients thereof. However, a quiesced node must continue to route any data messages or control messages which it receives from other nodes of the network.

25 In one embodiment, the following messages are used to quiesce a network in accordance with the present invention.

- QUIESCE - sent by the root of a configuration change to initiate quiescence of data messages.

- CONFIGURE - sent by a configuration manager and nodes in the network to change a spanning tree used to route messages in the network.
- 5 • QUIESCE_ACK - sent by a node to acknowledge receipt of a QUIESCE message. Once a QUIESCE_ACK has been sent, a node cannot forward messages from clients into the routing network any new data messages for transmission across the network. However, it must continue to route all data and control messages sent by other nodes in the network.
- 10 • QUIESCE_SPECIAL - sent by a root to quiesce a special node, such as a logging node or a sequencing node. The special node responds with a QUIESCE_SPECIAL_ACK message.
- 15 • QUIESCE_COMPLETE - sent by the root to indicate that all nodes have been quiesced and the new configuration may be resumed.

20 An overview of the algorithm for quiescing and reconfiguring a broker network is given next. First, a decision is made to reconfigure the broker network. This decision is outside of the scope of this description. This description assumes that a CONFIGURE message is communicated to a node in the network which becomes the root of the configuration change.

25 For example, a Configuration Manager (described below) under control of some administrator might calculate a new configuration for the network and send a CONFIGURE message to the root. Parent and child nodes are defined in relationship to this root node.

In one embodiment, quiescent reconfiguration in accordance with this invention can then proceed in three phases. First, data messages within the network are quiesced. Second, control messages (protocol messages used
5 by special nodes, i.e., loggers and sequencers, e.g., LACK/SACK messages) are quiesced. Third, the network is reconfigured. These phases are summarized below.

Data Message Quiescence

The root node initiates quiescence by sending a QUIESCE
10 message to all child nodes thereof using the existing configuration. When a node receives a QUIESCE message, the node begins queueing new data messages received from its clients, forwards the QUIESCE message to all child nodes, and sends a QUIESCE_ACK to its parent. QUIESCE_ACK messages
15 may be coalesced at each level (i.e., a parent may wait to receive QUIESCE_ACKs from all of its children before sending its own QUIESCE_ACK to its parent), or all QUIESCE_ACK messages may be forwarded to the root node. Once quiesced, a node does not forward any new data messages from clients
20 thereof. However, the node continues to forward data and control messages received from neighboring nodes (parents and children). Also, a logging/sequencing node continues to produce LACK/SACK messages in response to data messages which it receives.

25 Once the root node has received a QUIESCE_ACK message from all nodes, from the root's perspective, all data messages have been quiesced, and there can be no data messages flowing through the network towards the root. However, there may be data messages flowing away from the

root node. Also, there may be SACK and LACK messages flowing towards and away from the root node.

Control Message Quiescence

5 The root node next quiesces LACK/SACK messages in the network. Using the same quiesce technique outlined above, the root node sends QUIESCE_SPECIAL messages to any children sequencers and loggers. Note that if the root node is the only special node in the network, the control message quiescence phase is not necessary. When a logger/sequencer
10 receives a QUIESCE_SPECIAL message, the node will not receive any new data messages on the current configuration. When all LACK/SACK messages to any previous data messages have been sent, the logging/sequencing node sends a QUIESCE_SPECIAL_ACK to the root node. After a
15 logger/sequencer node has been quiesced, the node continues to forward any control messages received from neighboring nodes (parent and children).

Once the root has received a QUIESCE_SPECIAL_ACK message from all logger/sequencer nodes, then from the
20 root's perspective, all control messages have been quiesced and there are no control messages flowing through the network towards the root node. However, there may still be data and control messages flowing away from the root node.

Reconfiguration

25 The root next informs all nodes that the network has been quiesced and proceeds to reconfigure the network. First, the root node sends a QUIESCE_COMPLETE to all nodes

using the existing configuration. Because links between nodes are FIFO, the QUIESCE_COMPLETE message is guaranteed to be the last message in the existing configuration, i.e., no data or control message can follow the QUIESCE_COMPLETE message. Next, the root of the new configuration (if different from the old root, the old root would have to send a message to the new root), sends a CONFIGURE message to all nodes using the new configuration. When a node receives a CONFIGURE message, the node forwards the message to all of its downstream nodes in the new configuration. If a node receives a CONFIGURE message before it has received a QUIESCE_COMPLETE message on the previous configuration, the node must wait for the QUIESCE_COMPLETE before processing any new messages received on the new configuration. Waiting for the QUIESCE_COMPLETE message insures that all data and control messages have been received on the old configuration. Once a QUIESCE_COMPLETE message is received, any resources allocated for the previous configuration are no longer needed and may be freed.

One detailed embodiment of quiescent reconfiguration in accordance with the present invention is described below with reference to **Figs. 5-12**. **Fig. 5** depicts one example of additional information employed at the routers of a network to use quiescent reconfiguration in accordance with this invention. For example, the table of **Fig. 5** could be associated with or incorporated within the quiescent reconfiguration component 405 of the router of **Fig. 4**. This table includes (in one example) entries for five variables, labeled RECONFIG_ROOT, QUIESCING, CONFIGURE_RECEIVED, QUIESCE_MSG_QUEUE, and QUIESCING_CHILDREN. Each of these

variables is described below in connection with the flowchart process of **Figs. 6-12**.

Fig. 6 depicts one embodiment for processing a CONFIGURE message received, for example, from a configuration manager. As noted above, an assumption is made that the configuration manager independently makes the decision to effect a particular topology change, i.e., a reconfiguration. A configuration manager is a "network system service" that is responsible for maintaining information about the structure, function and status of a network system. This includes information such as the network topology, nodes with certain properties (such as loggers, sequencers), quality of service offered by nodes in the network, etc. A system's configuration may be statically fixed or dynamically changing. A configuration manager may be centralized or distributed. Network system management products such as IBM's Tivoli TME-10 contain configuration management components. Again, from the perspective of the current invention, a CONFIGURE message is assumed to be received from the configuration manager. The present invention is directed to a technique by which reconfiguration is transparent to the publishers and subscribers of the network, particularly where the network employs a special logging or sequencing node as described above.

Referring to **Fig. 6**, processing commences with receipt of a CONFIGURE message 600 within the network. With receipt of this message, the node determines whether it is the root of the reconfiguration 605. If "no", then the CONFIGURE message is forwarded to all children nodes in the new

configuration 610, and the node determines whether the QUIESCING state is true 615. If "yes", then the CONFIGURE_RECEIVED indicator is set 620. Otherwise, the reconfiguration is complete and the node begins forwarding
5 messages from its message queue (QUIESCE_MSG_QUEUE) using the new spanning tree 630.

Returning to inquiry 605, if the node is the root of the reconfiguration, then the node's RECONFIGURE_ROOT indicator is set 640, as well as the QUIESCING indicator
10 650. A QUIESCE message is sent to all children in the current configuration 660 and the QUIESCING_CHILDREN indicator is set to the number of children nodes in the current configuration 670. If the QUIESCING_CHILDREN count is zero 680, then processing jumps to step 850 of **Fig. 8**
15 (described below).

Fig. 7 is a flowchart of one embodiment for QUIESCE message processing in accordance with the present invention. When a node receives a QUIESCE message 700, the node's QUIESCING indicator 710 is set, and the CONFIGURE_RECEIVED
20 indicator is reset 720. The QUIESCE message is forwarded to downstream routing nodes 730 and the QUIESCE_CHILDREN count is set to the number of downstream routing nodes 740. If the QUIESCE_CHILDREN count is zero, then the QUIESCE_ACK message is returned to the node's parent node 750.

25 One embodiment for processing (pursuant to the present invention) a QUIESCE_ACK message is depicted in **Fig. 8**. Upon receipt of a QUIESCE_ACK message 800 at a node, the node's QUIESCING_CHILDREN count is decremented 810 and the node determines whether the QUIESCING_CHILDREN count is zero

820. If "no", then (in this embodiment) the node awaits further QUIESCE_ACK messages, meaning that the current processing is done 830.

Once all children have responded with a QUIESCE_ACK message, the node determines whether it is the reconfiguration root 840. If "no", the node sends a QUIESCE_ACK to its parent node 845. If the node is the root node for the reconfiguration, then the node sends a QUIESCE_SPECIAL message to its children nodes having a special node in its sub-tree 850. Also, note from **Fig. 8**, that if the QUIESCING_CHILDREN count is zero in step 680 of **Fig. 6**, then processing jumps to instruction 850. After sending the QUIESCE_SPECIAL message, the node sets the QUIESCING_CHILDREN count to the number of children to which the QUIESCE_SPECIAL message was sent 860. If the QUIESCING_CHILDREN count equals zero 870, then processing goes to step 1050 of **Fig. 10**.

Fig. 9 depicts a node's processing of a QUIESCE_SPECIAL message in accordance with the present invention. After a QUIESCE_SPECIAL message is received at a node 900, the node forwards the message to appropriate children nodes if a special node exists in a sub-tree from that node 910. The QUIESCING_CHILDREN indicator is set to the number of children nodes to which the QUIESCE_SPECIAL message is forwarded 920. If the QUIESCING_CHILDREN indicator equals zero, then a QUIESCE_SPECIAL_ACK message is returned to the node's parent node 930.

One embodiment for processing the QUIESCE_SPECIAL_ACK message is depicted in **Fig. 10**. Upon receipt of a

QUIESCE_SPECIAL_ACK message at a node 1000, the node decrements its QUIESCING_CHILDREN count 1010, and determines whether the QUIESCING_CHILDREN count is zero 1020. If "no", this processing is done 1025. Otherwise, the node
5 determines whether it is the root node for the reconfiguration 1030. If "no", then a QUIESCE_SPECIAL_ACK message is sent to its parent node 1040.

If the root comprises the reconfiguration root, or if the node's QUIESCING_CHILDREN count equals zero (step 870 of
10 **Fig. 8**), processing sends a QUIESCE_COMPLETE message to the node's children in the old configuration 1050. In addition, a CONFIGURE message is sent to the children in the new configuration 1060, and the RECONFIGURE_ROOT and QUIESCING indicators are reset 1070. The node then processes any
15 messages in the QUIESCE_MSG_QUEUE 1080.

Fig. 11 depicts one embodiment for processing a QUIESCE_COMPLETE message in accordance with the principles of the present invention. Upon a node's receipt of a QUIESCE_COMPLETE message 1100, the node resets the QUIESCING
20 indicator 1110. The QUIESCE_COMPLETE message is then forwarded to its children nodes with respect to the current spanning tree 1120. The node inquires whether the CONFIGURE_RECEIVED indicator is set 1130 and, if not, processing is completed 1140. Otherwise, the
25 reconfiguration is complete and the node begins forwarding any messages from the QUIESCE_MSG_QUEUE using the new spanning tree 1150.

Fig. 12 depicts one embodiment for processing published messages in accordance with the present invention. Upon

receipt of a published message 1200, a node determines whether the QUIESCING indicator is set 1210. If "no", then the message is processed normally 1220. If in quiescing state, and the message is received from a local client or
5 the current node is the reconfiguration root node and the message is received from a parent node, the message is added to the node's QUIESCE_MSG_QUEUE 1250. Otherwise, the message is processed normally 1240.

Those skilled in the art will note from the description
10 provided herein that if configuration changes are confined to a sub-tree of the routing network, it is possible to confine the above-described processing to that sub-tree. In such a case, the root is the parent node of the sub-tree under which all configuration changes occur. If the sub-
15 tree does not contain a logger/sequencer, it is not necessary to quiesce the logger/sequencers. In such a case, the control message quiescence phase may be skipped. If the sub-tree does contain logger/sequencer node(s), the logger/sequencer nodes within the sub-tree must be quiesced.
20 So, the control message quiescence phase would be performed. Unlike the above description, data messages may be sent to the root by the parent of the root after data messages have been quiesced in the sub-tree. In this case, these data messages should be queued at either the root of the sub-
25 tree, or at the logger/sequencer nodes (this would only be possible if a logger/sequencer maintained the same function in the new configuration). Logging acknowledgment or sequencing acknowledgment messages must not be sent in response to these data messages until after the network has
30 been reconfigured.

Also, those skilled in the art will note from the description provided herein that if there are multiple spanning trees within the routing network and if configuration changes are required to more than one spanning tree, it is possible to extend the above-described processing to effect these changes simultaneously.


The present invention can be included, for example, in an article of manufacture (e.g., one or more computer program products) having, for instance, computer usable media. This media has embodied therein, for instance, computer readable program code means for providing and facilitating the capabilities of the present invention. The articles of manufacture can be included as part of the computer system or sold separately.

Additionally, at least one program storage device readable by machine, tangibly embodying at least one program of instructions executable by the machine, to perform the capabilities of the present invention, can be provided.

The flow diagrams depicted herein are provided by way of example. There may be variations to these diagrams or the steps (or operations) described herein without departing from the spirit of the invention. For instance, in certain cases, the steps may be performed in differing order, or steps may be added, deleted or modified. All of these variations are considered to comprise part of the present invention as recited in the appended claims.

While the invention has been described in detail herein in accordance with certain preferred embodiments thereof,

many modifications and changes therein may be effected by those skilled in the art. Accordingly, it is intended by the appended claims to cover all such modifications and changes as fall within the true spirit and scope of the
5 invention.



Claims

1 1. A method for reconfiguring a routing network
2 comprising:

3 quiescing the routing network to preserve a first-
4 in first-out ordering of data messages within the
5 routing network; and

6 reconfiguring the quiesced routing network.

1 2. The method of claim 1, wherein said quiescing
2 further comprising quiescing control messages within said
3 routing network prior to said reconfiguring.

1 3. The method of claim 2, wherein said routing
2 network comprises at least one of a logging network or a
3 sequencing network, said logging network including logging a
4 message to persistent storage within the routing network
5 prior to delivery of the message to one or more clients of
6 the network, and said sequencing network comprising
7 sequencing a message at a node of the routing network with
8 other messages received by the network prior to delivery of
9 the message to one or more clients of the network, wherein
10 said quiescing of said control messages comprises quiescing
11 any new logging acknowledgment message or sequencing
12 acknowledgment message within said logging network or
13 sequencing network, respectively.

1 4. The method of claim 1, wherein said quiescing
2 comprises sending a quiesce message from a root node to all
3 children nodes thereof using an existing routing network
4 configuration.

1 5. The method of claim 4, wherein when a node of said
2 routing network receives the quiesce message, the node
3 begins queuing any new data messages received from a client
4 thereof, forwards the quiesce message to any children nodes
5 thereof, and sends a quiesce acknowledgment to its parent
6 node, and wherein once the root node has received a quiesce
7 acknowledgment from all children nodes, all data messages in
8 a sub-tree defined from the root node have been quiesced.

1 6. The method of claim 1, wherein said routing
2 network is part of a publish/subscribe system, and wherein
3 said reconfiguring is transparent to both publishers and
4 subscribers of said publish/subscribe system.

1 7. The method of claim 1, wherein said routing
2 network comprises a continuously available broker network.

1 8. The method of claim 1, wherein said quiescing
2 comprises propagating a quiesce message from a root node
3 across a spanning tree of said routing network, said quiesce
4 message preventing any new data messages from being
5 published for routing across said spanning tree.

1 9. The method of claim 8, wherein each node of said
2 spanning tree responds to said quiesce message by sending a
3 quiesce acknowledgment message to its parent node, and
4 wherein after sending said quiesce acknowledgment message,
5 any new data message received from a client of said node is
6 queued at said node.

1 10. The method of claim 9, further comprising
2 quiescing control messages within said routing network prior
3 to said reconfiguring.

1 11. The method of claim 10, wherein said quiescing of
2 control messages comprises sending a quiesce special message
3 from said root node to a special node of said routing
4 network, said special node of said routing network
5 comprising one of a logger node or a sequencer node.

1 12. The method of claim 11, wherein upon receipt of
2 said quiesce special message at said special node, said
3 special node returns a quiesce special acknowledgment
4 message to said root node, and wherein upon receipt of said
5 root node of said quiesce special acknowledgment message,
6 said control messages within said routing network have been
7 quiesced.

1 13. The method of claim 9, wherein said reconfiguring
2 comprises sending a quiesce complete message from said root
3 node to nodes of said spanning tree, wherein said spanning
4 tree comprises an existing spanning tree configuration, and
5 then sending a configure message to said nodes using a new
6 spanning tree configuration, thereby accomplishing said
7 reconfiguration.

1 14. The method of claim 1, wherein said quiescing
2 further comprises quiescing control messages within said
3 routing network prior to said reconfiguring, and said
4 reconfiguring comprises reconfiguring said quiesced routing
5 network transparent to any clients of said routing network,
6 and wherein said routing network comprises one of a logging
7 routing network wherein messages are logged for guaranteed
8 delivery, or a sequencing routing network wherein messages
9 are sequenced for ordered delivery.

1 15. The method of claim 14, wherein said network is
2 part of a publish/subscribe system supporting content-based
3 subscription, and wherein said method is used in combination
4 with a method for routing messages within said routing
5 network, said method for routing comprising routing a
6 message to one or more clients of said network, said routing
7 being based on data content of said message irrespective of
8 any destination information that may be within said message.

1 16. The method of claim 15, wherein said routing
2 comprises logging said message at at least one logging node
3 within said network before delivering said message to said
4 one or more clients of said network, said logging comprising
5 storing said message in persistent storage.

1 17. The method of claim 14, further in combination
2 with a method for routing messages within the routing
3 network, said routing method comprising sequencing a message
4 at a node of the routing network with other messages
5 received by the routing network to produce an ordering of
6 message delivery within the routing network, and delivering
7 the message to one or more clients of the routing network
8 while maintaining the ordering of message delivery.

1 18. The method of claim 17, wherein said network is
2 part of a publish/subscribe system.

1 19. A system for reconfiguring a routing network
2 comprising:

3 means for quiescing the routing network to
4 preserve a first-in first-out ordering of data messages
5 within the routing network; and

6 means for reconfiguring the quiesced routing
7 network.

1 20. The system of claim 19, further comprising means
2 for quiescing control messages within said routing network
3 prior to reconfiguration thereof.

1 21. The system of claim 20, wherein said routing
2 network comprises at least one of a logging network or a
3 sequencing network, said logging network including a special
4 logger node for logging a message to persistent storage
5 within the routing network prior to delivery of the message
6 to one or more clients of the network, and said sequencing
7 network comprising a special sequencing node for sequencing
8 a message within the routing network with other messages
9 received by the network prior to delivery of the message to
10 one or more clients of the network, wherein the means for
11 quiescing of the control messages comprises means for
12 quiescing any new logging acknowledgment message or
13 sequencing acknowledgment message within the logging network
14 or sequencing network, respectively.

1 22. The system of claim 19, wherein said means for
2 quiescing comprises means for sending a quiesce message from
3 a root node to all children nodes thereof using an existing
4 routing network configuration.

1 23. The system of claim 22, further comprising means
2 for queueing any new data messages received from a client of
3 a node after the node receives the quiesce message, and for
4 forwarding the quiesce message to any children nodes of said
5 node, and for sending a quiesce acknowledgment to its parent
6 node, wherein once the root node has received a quiesce
7 acknowledgment from all children nodes, all data messages in
8 a sub-tree defined from the root node have been quiesced.

1 24. The system of claim 19, wherein said routing
2 network is part of a publish/subscribe system, and wherein
3 said means for reconfiguring comprises means for
4 reconfiguring the quiesced routing network transparent to
5 both publishers and subscribers of said publish/subscribe
6 system.

1 25. The system of claim 19, wherein said routing
2 network comprises a continuously available broker network.

1 26. The system of claim 19, wherein said means for
2 quiescing comprises means for propagating a quiesce message
3 from a root node across a spanning tree of said routing
4 network, said quiesce message preventing any new data
5 messages from being published for routing across said
6 spanning tree.

1 27. The system of claim 26, further comprising means,
2 at nodes of said spanning tree, for sending a quiesce
3 acknowledgment message to its parent node in response to
4 receipt of said quiesce message, and for queueing any new
5 data message received from a client of said node after
6 sending said quiesce acknowledgment message.

1 28. The system of claim 27, further comprising means
2 for quiescing control messages within said routing network
3 prior to said reconfiguration by said means for
4 reconfiguring.

1 29. The system of claim 28, wherein said means for
2 quiescing control messages comprises means for sending a
3 quiesce special message from said root node to a special
4 node of said routing network, said special node of said
5 routing network comprising one of a logger node or a
6 sequencer node.

1 30. The system of claim 29, further comprising means
2 for returning a quiesce special acknowledgment message from
3 said special node upon receipt of said quiesce special
4 message, wherein said routing network has been quiesced upon
5 receipt at said root node of said quiesce special
6 acknowledgment message.

1 31. The system of claim 27, wherein said means for
2 reconfiguring comprises means for sending a quiesce complete
3 message from said root node to nodes of said spanning tree,
4 wherein said spanning tree comprises an existing spanning
5 tree configuration, and thereafter, for sending a configure
6 message to nodes of a new spanning tree configuration,
7 thereby accomplishing said reconfiguration.

1 32. The system of claim 19, wherein said means for
2 quiescing further comprises means for quiescing control
3 messages within said routing network prior to said
4 reconfiguration by said means for reconfiguring, and said
5 means for reconfiguring comprises means for reconfiguring
6 said quiesced routing network transparent to any clients of
7 said routing network, and wherein said routing network
8 comprises one of a logging network wherein messages are
9 logged for reliable routing, or a sequencing network wherein
10 messages are sequenced for ordered delivery.

1 33. The system of claim 32, wherein said network is
2 part of a publish/subscribe system supporting content-based
3 subscription, and wherein said system is used in combination
4 with a system for routing messages within said routing
5 network, said system for routing messages comprising means
6 for routing a message to one or more clients of said
7 network, said means for routing being based on data content
8 of said message irrespective of any destination information
9 within said message.

1 34. The system of claim 33, wherein said means for
2 routing comprises means for logging said message at at least
3 one logging node of said network before delivering said
4 message to said one or more clients of said network, said
5 means for logging comprising means for storing said message
6 in persistent storage.

1 35. The system of claim 32, further in combination
2 with a system for routing messages within the routing
3 network, said routing system comprising means for sequencing
4 a message at a node of the routing network with other
5 messages received by the routing network to produce an
6 ordering of message delivery within the routing network, and
7 means for delivering the message to one or more clients of
8 the routing network while maintaining the ordering of
9 message delivery.

1 36. The system of claim 35, wherein said routing
2 network is part of a publish/subscribe system.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
221

1 37. A system for reconfiguring a publish/subscribe
2 system comprising:

3 a routing network adapted to receive published
4 messages for forwarding to subscribers; and

5 said network being further adapted to quiesce data
6 messages and control messages within said network in
7 response to a reconfigure command to preserve a first-
8 in first-out ordering of data and control messages
9 within the routing network, and to then reconfigure the
10 routing network once data messages and control messages
11 have been quiesced.

12

1 38. An article of manufacture comprising:

2 at least one computer usable medium having
3 computer readable program code means embodied therein
4 for effecting reconfiguring of a routing network, the
5 computer readable program code means in the article of
6 manufacture comprising:

7 computer readable program code means for
8 causing a computer to effect quiescing the routing
9 network to preserve a first-in first-out ordering
10 of data messages within the routing network; and

11 computer readable program code means for
12 causing a computer to effect reconfiguring the
13 quiesced routing network.

1 39. The article of manufacture of claim 38, wherein
2 said routing network is part of a publish/subscribe system.

1 40. The article of manufacture of claim 39, wherein
2 said publish/subscribe system includes at least one special
3 node within said routing network, said at least one special
4 node comprising one of a logging node or a sequencing node,
5 wherein said logging node is employed to log messages to
6 persistent storage, and said sequencing node is employed to
7 sequence messages for ordered delivery.

1 41. The article of manufacture of claim 40, wherein
2 said computer readable program code means for causing a
3 computer to effect reconfiguring comprises computer readable
4 program code means for causing a computer to effect
5 reconfiguring the quiesced routing network transparent to
6 both publishers and subscribers of said publish/subscribe
7 system.

* * * * *

QUIESCENT RECONFIGURATION OF A ROUTING NETWORK

Abstract of the Disclosure

Reconfiguration of a continuously available routing
5 network of a publish/subscribe system is achieved by
quiescing data messages and control messages within the
routing network to preserve first-in first-out ordering
thereof, and then, reconfiguring the quiesced routing
network. This reconfiguration technique is particularly
10 applicable to a routing network having at least one special
node comprising one of a logger node or a sequencer node,
wherein the logger node is used to store a message to
persistent storage within the routing network prior to
delivery of the message to one or more clients, and the
15 sequencer sequences a message with other messages received
by the network prior to delivery thereof for ordered
delivery of the messages to one or more clients of the
network.

“SECRET”






fig. 1








fig. 4

RECONFIG_ROOT	TRUE/FALSE
QUIESCING	TRUE/FALSE
CONFIGURE_RECEIVED	TRUE/FALSE
QUIESCE_MSG_QUEUE	FIFO QUEUE
QUIESCING_CHILDREN	No.

fig. 5




fig. 6




fig. 7




fig. 8





fig. 9






fig. 11




fig. 12

Docket No.
YO998-527

Declaration and Power of Attorney For Patent Application

English Language Declaration

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

QUIESCENT RECONFIGURATION OF A ROUTING NETWORK

the specification of which

(check one)

☒ is attached hereto.

☐ was filed on _____ as United States Application No. or PCT International Application Number _____ and was amended on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119(a)-(d) or Section 365(b) of any foreign application(s) for patent or inventor's certificate, or Section 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)

Priority Not Claimed

_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>
_____ (Number)	_____ (Country)	_____ (Day/Month/Year Filed)	<input type="checkbox"/>

I hereby claim the benefit under 35 U.S.C. Section 119(e) of any United States provisional application(s) listed below:

(Application Serial No.)

(Filing Date)

(Application Serial No.)

(Filing Date)

(Application Serial No.)

(Filing Date)

I hereby claim the benefit under 35 U. S. C. Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. Section 112, I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, C. F. R., Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

(Application Serial No.)

(Filing Date)

(Status)
(patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. *(list name and registration number)*

Manny W. Schechter - Reg. No. 31,722

Terry J. Ilardi - Reg. No. 29,936

Christopher A. Hughes - Reg. No. 26,914

Edward A. Pennington - Reg. No. 32,588

John E. Hoel - Reg. No. 26,279

Joseph C. Redmond, Jr. - Reg. No. 18,753

Kevin M. Jordan - Reg. No. 40,277

Stephen C. Kaufman - Reg. No. 29,551

Jay P. Sbrolini - Reg. No. 36,266

David M. Shofi - Reg. No. 39,835

Robert M. Trepp - Reg. No. 25,933

Louis P. Herzberg - Reg. No. 41,500

Daniel P. Morris - Reg. No. 32,053

Douglas W. Cameron - Reg. No. 31,596

Paul J. Otterstedt - Reg. No. 37,411

Send Correspondence to: **Kevin P. Radigan, Esq.**
HESLIN & ROTHENBERG, P.C.
5 Columbia Circle
Albany, NY 12203

Direct Telephone Calls to: *(name and telephone number)*

Kevin P. Radigan, Esq. - Tel.: (518) 452-5600

Full name of sole or first inventor

Kevan Lee Miller

Sole or first inventor's signature

Date

Residence

3 Kilian Drive, Danbury, CT 06811

Citizenship

United States of America

Post Office Address

3 Kilian Drive

Danbury, CT 06811

Full name of second inventor, if any

Robert Evan Strom

Second inventor's signature

Date

Residence

6 Rochambeau Ave., Ridgefield, CT 06877

Citizenship

United States of America

Post Office Address

6 Rochambeau Ave.

Ridgefield, CT 06877

Full name of third inventor, if any Daniel Charles Sturman	
Third inventor's signature	Date
Residence 408 Knickerbocker Road, Englewood, NJ 07631	
Citizenship United States of America	
Post Office Address 408 Knickerbocker Road	
Englewood, NJ 07631	

Full name of fourth inventor, if any Michael James Ward	
Fourth inventor's signature	Date
Residence 25 West Park Avenue, New Haven, CT 06511	
Citizenship United States of America	
Post Office Address 25 West Park Avenue	
New Haven, CT 06511	

Full name of fifth inventor, if any	
Fifth inventor's signature	Date
Residence	
Citizenship	
Post Office Address	

Full name of sixth inventor, if any	
Sixth inventor's signature	Date
Residence	
Citizenship	
Post Office Address	